

# DICENTIS Wireless Devices



[iprobolutions.com/conference systems](http://iprobolutions.com/conference systems)



**BOSCH**  
Invented for life



- ▶ 4.3 inch capacitive touch screen and built-in NFC reader for identifying users
- ▶ Option to display personalized custom logo on the touch screen
- ▶ Removable Battery Pack, easy to change and charge
- ▶ Configurable as a participant, dual-use or chairperson Wireless Device by use of web browser interface
- ▶ Functionality can be expanded with software modules without the need for hardware modification

The elegantly designed Wireless Devices (DCNM-WD and DCNM-WDE) of the DICENTIS Wireless Conference System enable participants to speak, register a request-to-speak, and listen to the speaker during a meeting.

Both devices can be easily configured as a single-use, dual-use or chairperson Wireless Device via the web browser interface of the Wireless Access Point (DCNM-WAP).

The Wireless Device Extended (DCNM-WDE) enables advanced meeting efficiency due to the 4.3 inch capacitive touch screen and Near Field Communication (NFC) reader for identifying users.

## Functions

### General

- The Wireless Devices connect to the DCNM-WAP.
- Single-use, dual-use or chairperson can be configured via the web browser interface.
- Audio mute button.
- Operates in the 2.4 GHz and 5 GHz (UNII1, 2 (extended) and 3) (license free) band.

### DCNM-WD

- Used for basic discussion.

### DCNM-WDE

The Wireless Device Extended, which enables extended discussion, has:

- 4.3 inch capacitive touch screen for displaying:
  - Custom logo.
  - Multiple user interface languages in original characters.
  - Speaker list.
  - Request list.
- Built-in Near Field Communication (NFC) contactless tag reader.
- Additional functionality by use of software modules only:
  - Identification functionality.
  - Voting.
  - Camera control.

### Speech intelligibility

- Maximum speech intelligibility is guaranteed at all times.
- The Wireless Devices connects to the DCNM-WAP.
- The Wireless Devices produce crystal-clear sound due to a very high signal-to-noise ratio and smart frequency selection.

- The loudspeaker and microphone can be active at the same time for a face-to-face meeting experience. To prevent acoustic feedback, a feedback suppressor is built-in.

### Zero Interference

- Based on standard WiFi.
- Seamless automatic frequency channel switching.
- WiFi coverage area range test.
- Packet Loss Concealment.

### Security

- The DICENTIS Wireless Conference System and Wireless Devices have secure connectivity using WPA2 to prevent eavesdropping and unauthorized access.
- Encryption ensures that information within the system remains confidential.

### Microphones

- A socket is provided to connect the pluggable microphone (DCNM-HDMIC, DCNM-MICS or DCNM-MICL, all to be ordered separately).

### Headphones and loudspeakers

- The Wireless Devices accommodate two headphone connections and controls (on the left and right-hand side), so the speaker can be heard clearly even with excessive background noise.

### Battery maintenance

- Rechargeable Battery Pack (DCNM-WLIION).
- The lithium-ion Battery Pack can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.
- Smart battery management via web browser interface control (battery status and usage counting time).

### Controls and Indicators

- On top side:
  - 4.3 inch capacitive display with touch screen (DCNM-WDE only).
  - Microphone with a red or green indicator:
    - **Red** indicates microphone is active.
    - **Green** indicates request-to-speak accepted.
  - LED indicators on device showing:
    - Microphone on state – **Red**.
    - Possible-to-speak – **White**.
    - Priority – **White** (Chairperson only).
    - Request-to-speak – **Green**.
- On the left and right hand side
  - Headphone rotary volume controls.
- On rear side:
  - Yellow out-of-range of Wireless Access Point LED indicator.
  - Red battery low LED indicator.
- Under base side:
  - Recessed, so called ‘De-init,’ switch to disconnect the connected Wireless Device with the Wireless Access Point (DCNM-WAP).

### Interconnections

- Socket for pluggable microphone.
- Two 3.5 mm (0.14 in) headphone sockets stereo jack type.

## Certifications and approvals

EU	CE
US	FCC
CA	ICES-003
KR	KC
AU/NZ	RCM
RU/KZ/BY	EAC
JP	MIC
CN	China RoHS, CMIIT
SA	SASO
BR	ANATEL

Region	Certification
Europe	CE
	CE

## Parts included

Quantity	Components
1	DCNM-WD or DCNM-WDE Wireless Device

## Technical specifications

### Electrical

Supply voltage (battery pack)	7.5 Vdc
Power consumption	4.5 W
Operating time DCNM-WD	> 24 hours (20% speech, 80% listening)
Operating time DCNM-WDE	> 20 hours (20% speech, 80% listening)
Frequency response	100 Hz – 20 kHz (-3 dB at nominal level)
THD at nominal level	< 0.1 %
Dynamic range	> 90 dB
Signal-to-noise ratio	> 90 dB
Headphone load impedance	> 32 ohm < 1k ohm
Headphone output power	15 mW

### Radio

WiFi standard	IEEE 802.11n
Frequency Range	2.4 GHz and 5 GHz (ISM license free)

**Audio inputs**

Nominal microphone input	80 dB SPL according IEC60914
Maximum microphone input	110 dB SPL according IEC60914

**Audio outputs**

Loudspeaker nominal output	72 dB SPL at 0.5 m
Loudspeaker maximum output	80 dB SPL
Headphone nominal output	0 dBV
Headphone maximum output	3 dBV

**General**

Screen size (DCNM-WDE only)	4.3 inch
Screen type (DCNM-WDE only)	Capacitive multi-touch
Supported contactless NFC tag (DCNM-WDE only)	According to: ISO/IEC14443 Type A (from 106 kbps to 848 kbps. MIFARE 106kbps).

**Mechanical**

Mounting	Tabletop
Dimensions (H x W x D) without microphone	72 x 259 x 139 mm (2.8 x 10.2 X 5.5 in)
Weight: DCNM-WD DCNM-WD + Battery Pack DCNM-WDE DCNM-WDE + Battery Pack	590 g (1.30 Lb) 1051 g (2.32 lb) 670 g (1.47 lb) 1131 g (2.49 lb)
Color (top and base)	Traffic black (RAL 9017)

**Environmental**

Operating temperature	5 °C to +45 °C (41 °F to +113 °F)
Storage and transport temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Relative humidity	< 95 %, > 5%

**Ordering information****DICENTIS Wireless Device**

DICENTIS Wireless Device. Pluggable microphone and battery pack to be ordered separately.  
Order number **DCNM-WD**

**DICENTIS Wireless Device Extended**

DICENTIS Wireless Device Extended with 4.3 inch touch screen, NFC identification reader. Pluggable microphone and battery pack to be ordered separately.

Order number **DCNM-WDE**

**Accessories****DICENTIS Battery Pack**

Battery Pack for Wireless Device (DCNM-WD and DCNM-WDE), lithium-ion, 7.5 Vdc, 12800 mAh, color: Charcoal.

Order number **DCNM-WLIION**

**DICENTIS Transport Case for 8 XD**

Transport Case for storing and transporting 8 DICENTIS devices, 8 high directive microphones (DCNM-HDMIC), 8 short or long Stem Microphones (DCNM-MICS/L), and one Wireless Access Point (DCNM-WAP), if applicable.

Order number **DCNM-TC**

**DICENTIS High Directive Microphone**

DICENTIS High Directive Microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-HDMIC**

**DICENTIS Short Stem Microphone**

DICENTIS short stem microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-MICS**

**DICENTIS Long Stem Microphone**

DICENTIS long stem microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-MICL**

**ACD-MFC-ISO 50/each**

MIFARE Classic ID card with 1 kByte data storage, 2 application areas, one of which can be customized.

Packing information: 50 cards/ each unit

Order number **ACD-MFC-ISO**

**ACD-EV1-ISO 50/each**

Mifare DESFire EV1 ID card with 8 kByte data storage, 2 application areas, one of which can be customized.

Packing information: 50 cards/ each unit

Order number **ACD-EV1-ISO**

**Software Options****DICENTIS Voting at Seat**

DICENTIS software license for enabling voting at seat in the DICENTIS multimedia, DICENTIS discussion Extended, and DICENTIS wireless Extended.

Order number **DCNM-LSVT**

**DICENTIS Identification at Seat**

DICENTIS software license for enabling identification at seat in the DICENTIS discussion Voting, DICENTIS discussion Language, DICENTIS discussion Extended, DICENTIS multimedia Device, and DICENTIS wireless Extended.

Order number **DCNM-LSID**

**DICENTIS Dual Use at Seat**

DICENTIS software license for enabling dual-use at seat in the DICENTIS discussion Basic, DICENTIS discussion Language, DICENTIS discussion Extended, and DICENTIS wireless Extended.

Order number **DCNM-LSDU**

For more information, please visit  
<http://iprobesolutions.com/conference-systems/dicentis-wireless-conference-system>

Contact:

iProbe Multilingual Solutions, Inc.  
419 Park Avenue South, New York, NY  
10016 Tel. +1-212-489-6035  
Email: [info@iprobesolutions.com](mailto:info@iprobesolutions.com)  
[iprobesolutions.com](http://iprobesolutions.com)



iProbe is a authorized dealer for Bosch Security Systems, Inc.  
Specialties include conferencing and language distribution systems.

Represented by:

**Americas:**

Bosch Security Systems, Inc.  
12000 Portland Avenue South  
Burnsville MN 55337, USA  
Phone: +1-800-392-3497  
Fax: +1-800-955-6831  
[audiosupport@us.bosch.com](mailto:audiosupport@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
[emea.securitysystems@bosch.com](mailto:emea.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
[apr.securitysystems@bosch.com](mailto:apr.securitysystems@bosch.com)  
[www.boschsecurity.asia](http://www.boschsecurity.asia)

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
[www.boschsecurity.com.cn](http://www.boschsecurity.com.cn)

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
[latam.boschsecurity@bosch.com](mailto:latam.boschsecurity@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)